

SPECIALTY CARBON BLACKS

# VULCAN® XC200 Conductive Carbon Black



## **Product Highlights**

VULCAN XC200 conductive carbon black is part of our XC-family of conductive carbon blacks offering excellent conductivity, cleanliness, and consistency. Medium voltage (MV) compounds made with VULCAN XC200 conductive carbon black offer low strip force relative to other conductive carbon blacks. With outstanding cleanliness including low levels of ionic impurities, ash, and sulfur, VULCAN XC200 conductive carbon black can help enable long-term cable performance by minimizing potential sources of failure.

#### **Key Applications**

VULCAN XC200 conductive carbon black is suitable for use in insulation shields in medium voltage power cables where strippability is required or mandated. It's excellent cleanliness and conductivity performance allows for its use in conductor shields as well.

#### **Performance Features**

VULCAN XC200 conductive carbon black has several important features that help enable long-term performance of power cables and conductor shields:

- It is specifically designed to enable low strip force in strippable semicon shields
- It has good conductivity, protecting against premature cable failure
- It has excellent chemical and physical cleanliness for a smooth surface finish
- It has good processability and ease of dispersion

	Typical Properties	
PROPERTY	VALUES	TEST METHOD
lodine number (mg/g)	46	ASTM D-1510
OAN (cc/100g)	115	ASTM D-2414
325 mesh residue (ppm)	⟨10	ASTM D-1514
Ash (%)	⟨ 0.1	ASTM D-1506
Total Sulfur (%)	⟨ 0.75	ASTM D-1619

The data in the table above are typical test values intended as guidance only, and are not product specifications. Product specifications are available upon request from your Cabot representative.

### **Product Form & Logistics**

- Product Form: Pellets
- Regional Availability: Global
- Bag Packaging Options: 20 kg polyethylene or paper bags
- Bulk Packaging Options: 500 or 800 kg FIBC

Refer to the Material Safety Data Sheet (MSDS) for recommended storage conditions, available through your Cabot representative or on www.cabotcorp.com.





NORTH AMERICA

Cabot Corporation Business and Technical Center 157 Concord Road Billerica, MA 01821-7001

TEL +18004622313 FAX +1 978 670 7035

SOUTH AMERICA

Cabot Latin American Division Rue do Paraiso, 148 -5° ander 04103-000, Sao Paolo,

SP BRAZIL +55 11 2144 6400 TEL +55 11 3253 0051 FAX

**EUROPE** 

SIA Cabot Latvia 101 Mukusalas Street Riga, LV-1004, LATVIA

TEL +371 6705 0984 TEL +371 6705 0900 FAX +371 6705 0985

MIDDLE EAST/AFRICA

Cabot Specialty Chemicals Jebel Ali Free Zone LOB 15, Office 424

UNITED ARAB EMIRATES TEL +971 4 8871 800 FAX +971 4 8871 801

ASIA PACIFIC

Cabot China Ltd. 558 Shuangbai Road Shanghai 201108, CHINA

TEL +86 21 5175 8800 FAX +86 21 6434 5532 JAPAN

Cabot Specialty Chemicals, Inc. Sumitomo Chiba-Daimon Bldg. 3 F 2-5-5 Shiba Daimon, Minato-ku, Tokyo 105-0012, JAPAN

TEL +81 3 6820 0255 FAX +81 3 5425 4500

The data and conclusions contained herein are based on work believed to be reliable, however, Cabot cannot and does not guarantee that similar results and/or conclusions will be obtained by others. This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.